

CO2 távadó 4-20 mA kimenettel, légcsatornába

Termékkód: T5145

CO2 távadó 4-20 mA kimenettel. Légcsatornás beépítésre.



Green LED shines - CO2 concentration 0 to 1000 ppm

Yellow LED shines - CO2 concentration 1001 to 1200 ppm

Red LED shines - CO2 concentration 1201 ppm and more

[Optional CO₂ measuring range extension from the standard 0 to 5,000 ppm up to 0 to 10,000 ppm \(available at extra cost\):](#)

- **Extended measuring range:** 0 to 10 000 ppm
- **Accuracy in extended range:** 100 ppm + 5% of the measured value at 25 °C and 1013 hPa

Műszaki adatok

Range of CO ₂ concentration measurement	0 to 5000 ppm (optionally 10000 ppm)
Accuracy of CO ₂ concentration measurement	± (50 ppm + 3% from reading)
Temperature operating range	-30 to +60 °C
Humidity operating range (without condensation)	5 to 95 %RV
Pressure operating range	850 to 1100 hPa
IP protection	IP65 (electronics), IP20 (sensors)
Power	15-30 Vdc; 24 Vac
Dimensions	89 x 73 x 240 mm (W x H x L), stem length 130 mm
Weight	260 g
Warranty	3 years